

000000000		PPPPPPPPPPP		CCCCCCCCCCCCC		000000000		MMM		MMM
000000000		PPPPPPPPPPPPP		CCCCCCCCCCCCC		000000000		MMM		MMM
000000000		PPPPPPPPPPPPP		CCCCCCCCCCCCC		000000000		MMM		MMM
000	000	PPP	PPP	CCC		000	000	MMMMMM	MMMMMM	
000	000	PPP	PPP	CCC		000	000	MMMMMM	MMMMMM	
000	000	PPP	PPP	CCC		000	000	MMMMMM	MMMMMM	
000	000	PPP	PPP	CCC		000	000	MMM	MMM	MMM
000	000	PPP	PPP	CCC		000	000	MMM	MMM	MMM
000	000	PPP	PPP	CCC		000	000	MMM	MMM	MMM
000	000	PPPPPPPPPPPPP		CCC		000	000	MMM		MMM
000	000	PPPPPPPPPPPPP		CCC		000	000	MMM		MMM
000	000	PPPPPPPPPPPPP		CCC		000	000	MMM		MMM
000	000	PPP		CCC		000	000	MMM		MMM
000	000	PPP		CCC		000	000	MMM		MMM
000	000	PPP		CCC		000	000	MMM		MMM
000	000	PPP		CCC		000	000	MMM		MMM
000	000	PPP		CCC		000	000	MMM		MMM
000	000	PPP		CCC		000	000	MMM		MMM
000	000	PPP		CCC		000	000	MMM		MMM
	000000000	PPP		CCCCCCCCCCCCC			000000000	MMM		MMM
	000000000	PPP		CCCCCCCCCCCCC			000000000	MMM		MMM
	000000000	PPP		CCCCCCCCCCCCC			000000000	MMM		MMM

```
000000  PPPPPPP  CCCCCCCC  000000  MM  MM  DDDDDDDD  EEEEEEEEE  FFFFFFFF
000000  PPPPPPP  CCCCCCCC  000000  MM  MM  DDDDDDDD  EEEEEEEEE  FFFFFFFF
00  00  PP  PP  CC  00  00  MMMM  MMMM  DD  DD  EE  FF
00  00  PP  PP  CC  00  00  MMMM  MMMM  DD  DD  EE  FF
00  00  PP  PP  CC  00  00  MM  MM  DD  DD  EE  FF
00  00  PP  PP  CC  00  00  MM  MM  DD  DD  EE  FF
00  00  PPPPPPP  CC  00  00  MM  MM  DD  DD  EEEEEEE  FFFFFFFF
00  00  PPPPPPP  CC  00  00  MM  MM  DD  DD  EEEEEEE  FFFFFFFF
00  00  PP  CC  00  00  MM  MM  DD  DD  EE  FF
00  00  PP  CC  00  00  MM  MM  DD  DD  EE  FF
00  00  PP  CC  00  00  MM  MM  DD  DD  EE  FF
00  00  PP  CC  00  00  MM  MM  DD  DD  EE  FF
000000  000000  CCCCCCCC  000000  MM  MM  DDDDDDDD  EEEEEEEEE  FFFFFFFF
000000  000000  CCCCCCCC  000000  MM  MM  DDDDDDDD  EEEEEEEEE  FFFFFFFF
                                ....
                                ....
                                ....
                                ....
```

```
SSSSSSSS  DDDDDDDD  LL
SSSSSSSS  DDDDDDDD  LL
SS  DD  DD  LL
SS  DD  DD  LL
SS  DD  DD  LL
SSSSSS  DD  DD  LL
SSSSSS  DD  DD  LL
SS  DD  DD  LL
SS  DD  DD  LL
SS  DD  DD  LL
SSSSSSSS  DDDDDDDD  LLLLLLLLLL
SSSSSSSS  DDDDDDDD  LLLLLLLLLL
```



{ OPCOMDEF.SDL - system definition file for OPCOM internal structures

{ Version: 'V04-000'

{\*\*\*\*\*  
{\*  
{\* COPYRIGHT (c) 1978, 1980, 1982, 1984 BY  
{\* DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.  
{\* ALL RIGHTS RESERVED.  
{\*  
{\* THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED  
{\* ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE  
{\* INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER  
{\* COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY  
{\* OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY  
{\* TRANSFERRED.  
{\*  
{\* THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE  
{\* AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT  
{\* CORPORATION.  
{\*  
{\* DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS  
{\* SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.  
{\*  
{\*\*\*\*\*

{++

{ FACILITY: OPCOM - Operator Communications

{ ABSTRACT:

{ This file contains the SDL source for OPCOM internal structure  
{ definitions.

{ AUTHOR: CW Hobbs CREATION DATE: 27-Jun-1983

{ MODIFICATION HISTORY:

{ V03-003 CWH3169 CW Hobbs 5-May-1984  
{ Second pass for cluster-wide OPCOM:  
{ - Remove CLUSTER\_ENABLED bit, redo EFN numbers, add NODE\_LEAVING  
{ - Add BOD and COD structures  
{ - Add CSID to clm header & bump structure version numbers for clm structures  
{ V03-002 CWH3002 CW Hobbs 16-Sep-1983  
{ Add io error bit

{--

module OPCOMDEF;

```

/*
/* Define bit vector names for global status
/*
constant (
    SHUTDOWN_PENDING,      /* OPCOM is doing an orderly shutdown
    LOGGING_ENABLED,       /* Log events
    LAST_LOG_FAILED,       /* Last log attempt failed
    LOGFILE_CLOSED,        /* Logfile closed
    OLD_FORMAT_MSG,        /* This is an old format msg
    TIMESTAMP_PENDING,     /* Timestamp function pending
    BUSY,                  /* OPCOM is busy
    FLUSH_PENDING,         /* Must flush log file
    IN_VAXcluster          /* Member of VAXcluster
) equals 0 increment 1 prefix GBLSTS_;

/*
/* Define event flag numbers
/*
constant (
    ASYNCH,                /* Throwaway for asynch i/o
    BRKTHRU,               /* Break through service
    MAILBOX,               /* Mailbox reads
    TIME_STAMP             /* Timer ast
) equals 1 increment 1 prefix EFN_;

/*
/* Define the common data structure header fields.
/* All of the data structure definitions that follow
/* this one have the first few fields in common.
/* However, some of the fields are used differently,
/* depending on the type of data structure.
/*
aggregate HDR_AGGREGATE structure prefix HDR fill;
    FLINK      longword unsigned; /* FLink to next data structure
    BLINK      longword unsigned; /* BLink to last data structure
    SIZE       word unsigned;     /* Size of data structure
    TYPE       byte unsigned;     /* Type of data structure
    SCOPE      byte unsigned;     /* Scope of data structure
    SEQNUM     longword unsigned; /* Sequence # of data structure
    IDENT      longword unsigned; /* Cluster-wide ident (seqnum from original create)
    CSID       longword unsigned; /* Cluster system id
    NOD        longword unsigned; /* Pointer to NOD structure
    SCS_ID union fill;
        SYSTEMID character length 6; /* SCS System ID
        SCS_ID_S structure fill;
            SYSTEMIDL longword unsigned; /* Low order longword
            SYSTEMIDH word unsigned;     /* High order word
        end SCS_ID_S;
    end SCS_ID;
    FILLER     word unsigned;     /* Spare
    BPTR       longword unsigned; /* Back pointer to main data structure
/*
/* Define the common header status bits.
/* The low 16 bits are common for all data structures.
/* The high 16 bits are data structure specific.
/*

```



```
STATUS      structure longword unsigned;
  LAL        bitfield mask; /* Block is from LAL
  BRD        bitfield mask; /* Broadcast this message
  LOG        bitfield mask; /* Log this message
end STATUS;
```

```
end HDR_AGGREGATE;
```

```
/*
/* A system mailbox message contains a header. Here we will define
/* the offsets to the fields inside that header.
/*
```

```
aggregate MSG_AGGREGATE structure prefix MSG_ fill;
```

```
MSGTYPE      word unsigned; /* Message type code
REPLYMBX     word unsigned; /* Reply mailbox unit number
PRIVMASK1    longword unsigned; /* First LW of privilege mask
PRIVMASK2    longword unsigned; /* Second LW of privilege mask
SENDERUIC    longword unsigned; /* UIC of request sender
USERNAME     character length 12; /* Pointer to start of username
ACCOUNT      character length 8; /* Pointer to start of account
BASEPRI      byte unsigned; /* Sender's base priority
FILLER_2     byte unsigned fill; /* ** 1 spare byte **
```

```
end MSG_AGGREGATE;
```

```

/*
/* Define Request Context Block (RQCB) fields.
/*
aggregate RQCB_AGGREGATE structure prefix RQCB_ fill;

/*
/* common header
/*
    FLINK      longword unsigned;    /* Flink to next RQCB
    BLINK      longword unsigned;    /* Blink to last RQCB
    SIZE       word unsigned;        /* Size of data structure
    TYPE       byte unsigned;        /* Type of data structure
    FILLER_1   byte unsigned fill;   /* ** 1 spare byte **
    SEQNUM     longword unsigned;    /* RQCB sequence number

/*
/* Data above this mark is owned by the RQCB allocation routines
/*
    OVERLAY    character length 0;    /* Address where OK to change RQCB
    #overlay_mark = .;

/*
    IDENT      longword unsigned;    /* Cluster-wide ident (seqnum from original create)
    CSID       longword unsigned;    /* Cluster system id
    NOD        longword unsigned;    /* Pointer to NOD structure
    SCS_ID union fill;
        SYSTEMID character length 6; /* SCS System ID
        SCS_ID_S structure fill;
            SYSTEMIDL longword unsigned; /* Low order longword
            SYSTEMIDH word unsigned;     /* High order word
        end SCS_ID_S;
    end SCS_ID;
    FILLER     word unsigned;        /* Spare
    OCD        longword unsigned;    /* Backpointer to OCD

/*
/* Define request status bits.
/*
    STATUS     structure longword unsigned prefix RQSTS_;
        FILLER_1 bitfield length 16 fill;
        IMPCANCEL bitfield mask; /* Request implicitly canceled
    end STATUS;

/*
/* Following 38 bytes are copied from the system mailbox message header
/*
    MSGTYPE    word unsigned;        /* Message type code
    REPLYMBX    word unsigned;        /* Reply mailbox unit number
    PRIVMASK1   longword unsigned;    /* First LW of privilege mask
    PRIVMASK2   longword unsigned;    /* Second LW of privilege mask
    SENDERUIC   longword unsigned;    /* UIC of request sender
    USERNAME    character length 12;  /* Pointer to start of username
    ACCOUNT     character length 8;   /* Pointer to start of account
    BASEPRI     byte unsigned;        /* Sender's base priority
    FILLER_2    byte unsigned fill;   /* ** 1 spare byte **
    RQSTCODE    byte unsigned;        /* Request type code
    SCOPE       byte unsigned;        /* Scope of request
    OPTIONS     longword unsigned;    /* Request independent options
    RQ_OPTIONS  longword unsigned;    /* Request dependent options

```



```
ATTNMask1    longword unsigned;    /* Attention mask part 1
ATTNMask2    longword unsigned;    /* Attention mask part 2
RQSTID       longword unsigned;    /* User request identifier
UIC          longword unsigned;    /* Requestor UIC
/*
/* End of copied area, note that offset of MCB is used to determine end of copy
/*
MCB          longword unsigned;    /* Address of MCB
/*
RQSTNUM      longword unsigned;    /* Request number
USERNAMELEN  word unsigned;        /* Length of username, blanks trimmed
ACCOUNTLEN   word unsigned;        /* Length of account, blanks trimmed
/*
/* Define operator status bits.
/*
OPRSTS       structure word unsigned prefix OPRSTS_;
    TRM       bitfield mask;      /* Terminal
    REMTRM    bitfield mask;      /* Remote terminal
    MBX       bitfield mask;      /* Mailbox
    IMPDISABLE bitfield mask;      /* Operator implicitly disabled
end OPRSTS;

MBXSIZE      word unsigned;        /* Mailbox buffer size
OPER_LEN     longword unsigned;    /* Operator device name size
OPER_PTR     longword unsigned;    /* Operator device name pointer
TEXT_LEN     longword unsigned;    /* Optional text size
TEXT_PTR     longword unsigned;    /* Optional text pointer
DSBLFLINK    longword unsigned;    /* Flink to next disabled oper
DSBLBLINK    longword unsigned;    /* Blink to last disabled oper

constant SIZE equals .;            /* Size of RQCB in bytes
constant OVERLAY_SIZE equals .-#overlay_mark;

end RQCB_AGGREGATE;
```

```

/*
/* Define Request Control Block (RCB) fields.
/*
aggregate RCB_AGGREGATE structure prefix RCB_ fill;

/*
/* common header
/*
    FLINK      longword unsigned;    /* Flink to next RCB
    BLINK      longword unsigned;    /* Blink to last RCB
    SIZE       word unsigned;        /* Size of data structure
    TYPE       byte unsigned;        /* Type of data structure
    SCOPE       byte unsigned;       /* Scope of RCB
    SEQNUM     longword unsigned;    /* RCB sequence number
    IDENT      longword unsigned;    /* Cluster-wide ident (seqnum from original create)
    CSID       longword unsigned;    /* Cluster system id
    NOD        longword unsigned;    /* Pointer to NOD structure
    SCS_ID union fill;
        SYSTEMID character length 6; /* SCS System ID
        SCS_ID_S structure fill;
            SYSTEMIDL longword unsigned; /* Low order longword
            SYSTEMIDH word unsigned;    /* High order word
        end SCS_ID_S;
    end SCS_ID;
    FILLER     word unsigned;        /* Spare
    RQCB       longword unsigned;    /* Pointer to RQCB
    STATUS     longword unsigned;    /* Status longword

/*
    RQSTNUM    longword unsigned;    /* Operator request number
    TEXTLEN    longword unsigned;    /* Length of request text
    TEXTPTR    longword unsigned;    /* Address of request text

    constant SIZE equals .;          /* Size of RCB in bytes
end RCB_AGGREGATE;

```



```

/*
/* Define Operator Control Block (OCB) fields
/*
aggregate OCB_AGGREGATE structure prefix OCB_ fill;
/*
/* common header
/*
FLINK      longword unsigned;    /* Forward link to next OCB
BLINK      longword unsigned;    /* Backward link to last OCB
SIZE       word unsigned;        /* Size of OCB
TYPE       byte unsigned;        /* Type of data structure
SCOPE      byte unsigned;        /* Scope of OCB
SEQNUM     longword unsigned;    /* OCB sequence number
IDENT      longword unsigned;    /* Cluster-wide ident (seqnum from original create)
CSID       longword unsigned;    /* Cluster system id
NOD        longword unsigned;    /* Pointer to NOD structure
SCS_ID union fill;
  SYSTEMID character length 6;    /* SCS System ID
  SCS_ID_S structure fill;
    SYSTEMIDL longword unsigned;   /* Low order longword
    SYSTEMIDH word unsigned;       /* High order word
  end SCS_ID_S;
end SCS_ID;
FILLER     word unsigned;        /* Spare
RQCB       longword unsigned;    /* Address of RQCB
/*
/* Define OCB status bits.
/*
STATUS     structure longword unsigned;
  FILLER_1  bitfield length 16 fill;
  PRMOPR    bitfield mask;       /* Operator is permanent
  MAILBOX   bitfield mask;       /* Operator is a mailbox
end STATUS;
/*
ATTNMASK1  longword unsigned;    /* Operator attention mask
ATTNMASK2  longword unsigned;    /* Operator attention mask
DEVNAMLEN  longword unsigned;    /* Operator device name length
DEVNAMPTR  longword unsigned;    /* Operator device name string address
BUFSIZ     longword unsigned;    /* Operator device buffer size

constant SIZE equals .;          /* Size of OCB in bytes
end OCB_AGGREGATE;

```

```

/*
/* Define Operator Class Descriptor (OCD) fields.
/*
aggregate OCD_AGGREGATE structure prefix OCD_ fill;

/*
/* common header
/*
    FLINK      longword unsigned;    /* Flink to first OCB
    BLINK      longword unsigned;    /* Blink to last OCB
    SIZE       word unsigned;        /* OCD size
    TYPE       byte unsigned;        /* OCD type
    SCOPE      byte unsigned;        /* Scope of OCD
    SEQNUM     longword unsigned;    /* OCD sequence number
    IDENT      longword unsigned;    /* Cluster-wide ident (seqnum from original create)
    CSID       longword unsigned;    /* Cluster system id
    NOD        longword unsigned;    /* Pointer to NOD structure
    SCS_ID union fill;
        SYSTEMID character length 6; /* SCS System ID
        SCS_ID_S structure fill;
            SYSTEMIDL longword unsigned; /* Low order longword
            SYSTEMIDH word unsigned;     /* High order word
        end SCS_ID_S;
    end SCS_ID;
    FILLER     word unsigned;        /* Spare
    UIC        longword unsigned;    /* UIC associated w/ this OCD
/*
/* Define OCD status flags.
/*
    STATUS     structure longword unsigned;
        FILLER_1 bitfield length 16 fill;
        IMPCANCEL bitfield mask; /* At least one request was
                                /* implicitly canceled.
    end STATUS;
/*
    NOTIFYMASK1 longword unsigned; /* Operator notification mask
    NOTIFYMASK2 longword unsigned; /* Operator notification mask
    LCB         longword unsigned; /* Pointer to logfile control block
    FILLER_1    word unsigned fill; /* ** 2 spare bytes **
    RQSTCOUNT word unsigned;      /* Number of outstanding requests
    RQSTFLINK   longword unsigned; /* Flink to first request RQCB
    RQSTBLINK   longword unsigned; /* Blink to last request RQCB
    FILLER_2    word unsigned fill; /* ** 2 spare bytes **
    OPERCOUNT word unsigned;      /* Count of operators
    ATTNMASK1   longword unsigned; /* Operator attention mask1
    ATTNMASK2   longword unsigned; /* Operator attention mask2
    OPERFLINK   longword unsigned; /* FLINK to first OCB
    OPERBLINK   longword unsigned; /* BLINK to last OCB
    COUNTVECTOR character length 128; /* Count vector (64 words)

    constant SIZE equals .; /* Size of OCD in bytes
end OCD_AGGREGATE;

```



```

/*
/* Define the cluster node information block (NOD) offsets.
/*
aggregate NOD_AGGREGATE structure prefix NOD_ fill;

/*
/* common header
/*
FLINK      longword unsigned; /* FLINK to next NOD
BLINK      longword unsigned; /* BLINK to previous NOD
SIZE       word unsigned;    /* Size of data structure
TYPE       byte unsigned;    /* Type of data structure
FILL_1     byte unsigned;    /*
SEQNOM     longword unsigned; /* NOD sequence number
IDENT      longword unsigned; /* Cluster-wide ident (seqnum from original create)
CSID       longword unsigned; /* Cluster system id (for this host)
NOD        longword unsigned; /* Pointer to NOD structure
SCS_ID union fill;
  SYSTEMID character length 6; /* SCS System ID
  SCS_ID_S structure fill;
    SYSTEMIDL longword unsigned; /* Low order longword
    SYSTEMIDH word unsigned;    /* High order word
  end SCS_ID_S;
end SCS_ID;
STATE      byte unsigned;    /* State of the node
  constant ( /* Values for NOD_B_STATE, in form NOD_K_STATE_xxx
    STATE_LOCAL, /* This is the local node
    STATE_START, /* Recognized by $GETSYI, but hasn't responded to messages
    STATE_ACTIVE, /* Responded to messages, normally functioning partner
    STATE_DEPARTED /* Has disappeared from $GETSYI
  ) equals 1 increment 1;
  constant STATE_MAX equals NOD_K_STATE_DEPARTED;
FILL_2     byte unsigned;    /* Spare
FILL_3     longword unsigned; /*
STATUS     structure longword unsigned; /* Status longword
  FILLER_1 bitfield length 16 fill;
  ACK_PEND bitfield mask; /* Waiting for acknowledgement from this node
  ACK_ATTEMPTED bitfield mask; /* At least one ACK has been sent to this node
  IOERR_DISPLAYED bitfield mask; /* We have displayed an i/o error message
  NODE_LEAVING bitfield mask; /* Node is leaving the cluster, flush messages without signaling
end STATUS;

/*
NODE_CSID   longword unsigned; /* CSID for the node (for this NOD block)
NAME_DESC structure quadword unsigned; /* Desc for node name
  NAME_LEN longword unsigned; /* Name length
  NAME_PTR longword unsigned; /* Name address
end NAME_DESC;
NAME_BUF   character length 16; /* Buffer for actual name
SWINCARN   quadword unsigned; /* S/W incarnation number
SCS_ID union fill;
  NODE_SYSTEMID character length 6; /* SCS System ID
  SCS_ID_S structure fill;
    NODE_SYSTEMIDL longword unsigned; /* Low order longword
    NODE_SYSTEMIDH word unsigned;    /* High order word
  end SCS_ID_S;

```

```
end SCS_ID;  
constant SIZE equals .;  
end NOD_AGGREGATE;
```

```
/* Size of NOD in bytes
```



```

/*
/* Define the Message control block (MCB) offsets.
/*
aggregate MCB_AGGREGATE structure prefix MCB_ fill;

/*
/* common header
/*
FLINK      longword unsigned; /* FLINK to next MCB
BLINK      longword unsigned; /* BLINK to previous MCB
SIZE       word unsigned;    /* Size of data structure
TYPE       byte unsigned;    /* Type of data structure
SCOPE      byte unsigned;    /* Scope of MCB
SEQNUM     longword unsigned; /* MCB sequence number
IDENT      longword unsigned; /* Cluster-wide ident (seqnum from original create)
CSID       longword unsigned; /* Cluster system id
NOD        longword unsigned; /* Pointer to NOD structure
SCS_ID union fill;
  SYSTEMID character length 6; /* SCS System ID
  SCS_ID_S structure fill;
    SYSTEMIDL longword unsigned; /* Low order longword
    SYSTEMIDH word unsigned;    /* High order word
  end SCS_ID_S;
end SCS_ID;
FILLER     word unsigned;    /* Spare
RQCB       longword unsigned; /* Pointer to RQCB
STATUS     longword unsigned; /* Status longword
/*
MSGID      longword unsigned; /* Message Identifier
TEXTLEN    longword unsigned; /* Message text length
TEXTPTR    longword unsigned; /* Message text address
IOSB       longword unsigned; /* I/O status block

constant SIZE equals .; /* Size of MCB in bytes
end MCB_AGGREGATE;

```

```

/*
/* Define the BRKTHRU Output Descriptor (BOD) offsets.
/*
aggregate BOD_AGGREGATE structure prefix BOD_ fill;

/*
/* common header
/*
FLINK      longword unsigned; /* FLINK to next BOD
BLINK      longword unsigned; /* BLINK to previous BOD
SIZE       word unsigned;    /* Size of data structure
TYPE       byte unsigned;    /* Type of data structure
FILL_B     byte unsigned;    /*

/*
STATUS structure longword unsigned; /* Status longword
  DEAD      bitfield mask; /* BRKTHRU was very slow
  WAIT      bitfield mask; /* A REPLY /WAIT is being executed
  LOCAL_NODE bitfield mask; /* Target is on the local node
  SHORT_TIMEOUT bitfield mask; /* Use short timeout period
end STATUS;

/*
COMPLETION_ROUTINE address; /* Address of I/O completion routine
CSID      longword unsigned; /* CSID of remote node
NODDSC structure quadword unsigned; /* Node name descriptor
  NODLEN    longword unsigned; /* Node name length
  NODPTR    address; /* Node name address
end NODDSC;
TRMDSC structure quadword unsigned; /* Terminal name descriptor
  TRMLLEN  longword unsigned; /* Terminal name length
  TRMPTR   address; /* Terminal name address
end TRMDSC;

/*
/* Items for parameter list for actual call to $BRKTHRU
/*
MSGBUF structure quadword unsigned; /* MSGBUF parameter for call
  MSGLEN   longword unsigned; /* Message text length
  MSGPTR   address; /* Message text address
end MSGBUF;
SENDTO structure quadword unsigned; /* SENDTO parameter for call
  SENLEN   longword unsigned; /* Device name length
  SENPTR   address; /* Device name address
end MSGBUF;
SNDTYP    longword unsigned; /* Type code for send
IOSB structure quadword unsigned; /* I/O status block
  IOSB0    word unsigned;
  IOSB1    word unsigned;
  IOSB2    word unsigned;
  IOSB3    word unsigned;
end IOSB;
CARCON    longword unsigned; /* Carriage control
FLAGS     longword unsigned; /* Flags longword
REQID     longword unsigned; /* Requestor id

/*
QUETIME   quadword unsigned; /* Time that $BRKTHRU issued
SENBUFF   character length 64; /* Send name buffer

```



```
/*
  NODBUF      character length 16;  /* Node name buffer
  TRMBUF      character length 20;  /* Terminal name buffer
  constant SIZE equals .;          /* Size of BOD in bytes
end BOD_AGGREGATE;
```

```
/*
/* Define the Cluster Output Descriptor (COD) offsets.
/*
aggregate COD_AGGREGATE structure prefix COD_ fill;

/*
/* common header
/*
    FLINK      longword unsigned;    /* FLINK to next COD
    BLINK      longword unsigned;    /* BLINK to previous COD
    SIZE       word unsigned;        /* Size of data structure
    TYPE       byte unsigned;        /* Type of data structure
    FILL_B     byte unsigned;        /*
/*
    STATUS structure longword unsigned; /* Status longword
        DEAD      bitfield mask; /* EXE$CSP_CALL was very slow
    end STATUS;
/*
    CSID       longword unsigned;    /* CSID of remote node
    CSD        address;              /* CSD address
    NOD        address;              /* Address of the nod for the system
    ERRSTAT    longword unsigned;    /* Routine status code for error signal
    MSGBUF structure quadword unsigned; /* Message for remote node
        MSGLEN    longword unsigned; /* Message text length
        MSGPTR    address;            /* Message text address
    end MSGBUF;
/*
    QUETIME    quadword unsigned;    /* Time that EXE$CSP_CALL issued
/*
    constant SIZE equals .;          /* Size of COD in bytes
end COD_AGGREGATE;
```



```
/*
/* Define Structure Control Block (SCB) fields.
/* This control block contains information about all
/* data structures, and is used by the create and
/* delete data structure routines. Each data structure
/* is represented in the SCB table by an entry of the
/* following form. (LAL = Look Aside List)
/*
```

```
aggregate SCB_AGGREGATE structure prefix SCB_ fill;
```

```
SIZE      word unsigned;      /* Size of data structure
LAL_COUNT  word unsigned;      /* # of Look-aside list entries
SEQNUM     longword unsigned;  /* Count of blocks created
FLINK      longword unsigned;  /* Flink to first LAL entry
BLINK      longword unsigned;  /* Blink to last LAL entry

constant SIZE equals .;      /* Size of SCB in bytes
end SCB_AGGREGATE;
```

```
/*  
/* Define the Request Descriptor Block (RDB) fields. Each  
/* RDB structure contains some control information on a  
/* particular request. Each type of request that is known  
/* by OPCOM is represented by an RDB.  
/*
```

```
aggregate RDB_AGGREGATE structure prefix RDB_ fill;
```

```
    HANDLER    longword unsigned;    /* Address of request handler  
    COUNT      longword unsigned;    /* Count of requests received  
    OPTIONS     longword unsigned;    /* Options bit mask  
    ATTNMASK1   longword unsigned;    /* Operator attention mask  
    ATTNMASK2   longword unsigned;    /* Operator attention mask
```

```
    constant SIZE equals .;          /* Size of RDB in bytes  
end RDB_AGGREGATE;
```



```
/**
/* Cluster communications messages. These messages are sent between OPCOMs on
/* different nodes to implement cluster operations. These messages have a short
/* header which is identical for all messages.
/*-
```

```
/*
/* Define header for all cluster messages. This fills the first part of the message
/*
```

```
aggregate CLUSTER_MESSAGE structure prefix CLM_ fill;
```

RQSTCODE	byte unsigned;	/* Same as OPC\$B_RQSTCODE (OPC\$_X_CLUSMSG)
CLM_CODE	byte unsigned;	/* Cluster-specific request code
DS_VERSION	byte unsigned;	/* Version of data structure
SW_VERSION	byte unsigned;	/* Version of OPCOM software
LENGTH	word unsigned;	/* Size of structure
fill_1	word unsigned;	/* spare word */
CSID	longword unsigned;	/* CSID of sender

```
constant SIZE equals .;
```

```
end CLUSTER_MESSAGE;
```

```

/*
/* Define RPYBRD (REPLY broadcast) message fields. This message is sent from REPLY command
/* to OPCOM. OPCOM then sends the same packet to other nodes with a new request code.
/*

```

```

aggregate RPYBRD_MESSAGE structure prefix RPYBRD_ fill;

```

```

    CLM_HEADER character length CLM_K_SIZE fill;
    constant DS_VERSION equals 6;

```

```

/*
OPTIONS      structure word unsigned;
    ALL      bitfield mask;      /* /ALL involved
    BELL      bitfield mask;      /* /BELLS involved
    NODE      bitfield mask;      /* /NODE
    NOTIFY    bitfield mask;      /* Notify of any actions
    SHUTDOWN  bitfield mask;      /* /SHUTDOWN
    TERMINAL  bitfield mask;      /* /TERM involved
    URGENT    bitfield mask;      /* /URGENT
    USERNAME  bitfield mask;      /* /USER involved
    WAIT      bitfield mask;      /* /WAIT, do it locally
    BROAD_LOCAL bitfield mask;    /* Broadcast is going to local node
    BROAD_REMOTEALL bitfield mask; /* Broadcast is going to all remotes
    BROAD_REMOTELST bitfield mask; /* List of nodes (rpybrd_w_targ_node_len <> 0)
    LOCAL_NODE bitfield mask;    /* Command originated on the local node
end OPTIONS;

```

```

fill_2      word unsigned;

```

```

/*
/* Length fields point into the text area at the end of the block. Text
/* fields are concatenated at the end, in the same order as the length
/* fields.
/*

```

```

SEND_CSID      longword unsigned; /* CSID for sending node
SEND_TERM_LEN  word unsigned;      /* Terminal name of sender
SEND_USER_LEN  word unsigned;      /* User name of sender
SEND_NODE_LEN  word unsigned;      /* Name of sending node
MESSAGE_LEN    word unsigned;      /* Length of message text
OPTIONAL_OFF   word unsigned;      /* Offset to start of optional items
TARG_TERM_LEN  word unsigned;      /* Terminal name(s) of target terms
TARG_USER_LEN  word unsigned;      /* User name of target user(s)
TARG_NODE_LEN  word unsigned;      /* Name of target node(s)
TARG_NODE_OFF  word unsigned;      /* Offset to first node
fill_3      word unsigned;

```

```

/*
/* Formatted message buffer
/*

```

```

FORMAT_DESC structure quadword unsigned;
    FORMAT_LEN      longword unsigned;
    FORMAT_PTR      address;
end FORMAT_DESC;

```

```

constant MIN_SIZE equals .; /* Min message size

```

```

TEXT      character length 0; /* Text

```

```

end RPYBRD_MESSAGE;

```



```
/*
/* Define RPYNOT (REPLY broadcast notification) message fields. This message is sent from OPCOM
/* back to the node where a reply originated.
/*
```

```
aggregate RPYNOT_MESSAGE structure prefix RPYNOT_ fill;
```

```
    CLM_HEADER character length CLM_K_SIZE fill;
    constant DS_VERSION equals 2;
    /*
    /* Length fields point into the text area at the end of the block. Text
    /* fields are concatenated at the end, in the same order as the length
    /* fields.
    /*
    TERM_LEN          word unsigned;          /* Terminal name of sender
    MESSAGE_LEN       word unsigned;          /* Length of message text
    constant MIN_SIZE equals .;                /* Min message size
    TEXT              character length 0;      /* Text
    end RPYNOT_MESSAGE;
```

```
/*
/* Define SHUT message fields. This message is sent from OPCOM to remote nodes to
/* shut down opcom.
/*
```

```
aggregate SHUT_MESSAGE structure prefix SHUT_ fill;
```

```
    CLM_HEADER character length CLM_K_SIZE fill;
    constant DS_VERSION equals 3;
    constant MIN_SIZE equals .;                /* Min message size
    end SHUT_MESSAGE;
```

```

/*
/* Define CLMRQCB message fields. This message is sent between OPCOMs. The message
/* is essentially a copy of the OPCOM RQCB structure, except that all text strings
/* are concatenated to the end of the message (after the CLMRQCB_T_TEXT field).
/*

```

```

aggregate CLMRQCB_MESSAGE structure prefix CLMRQCB_ fill;

```

```

/*
/* The front part consists of the CLM header, then an entire RQCB block.
/*

```

```

CLM_HEADER character length CLM_K_SIZE fill;
constant DS_VERSION equals 2;
RQCB_OVERLAY character length RQCB_K_SIZE;

```

```

/*
/* Other information necessary to ship RQCBs between nodes
/*

```

```

MCB_MSGID longword unsigned; /* Message code from MCB
MCB_STATUS longword unsigned; /* Status code from MCB

```

```

/*
/* Length fields point into the text area at the end of the block. Text
/* fields are concatenated at the end, in the same order as the length
/* fields.
/*

```

```

constant MIN_SIZE equals .; /* Min message size

```

```

TEXT character length 0; /* Text

```

```

end CLMRQCB_MESSAGE;

```

```

/*
/* Define CLMACK message fields. This message is sent between OPCOMs to acknowledge
/* each other.
/*

```

```

aggregate CLMACK_MESSAGE structure prefix CLMACK_ fill;

```

```

/*
CLM_HEADER character length CLM_K_SIZE fill;
constant DS_VERSION equals 2;

```

```

/*
CSID longword unsigned; /* Cluster system id

```

```

SCS_ID union fill;

```

```

SYSTEMID character length 6; /* SCS System ID

```

```

SCS_ID_S structure fill;

```

```

SYSTEMIDL longword unsigned; /* Low order longword

```

```

SYSTEMIDH word unsigned; /* High order word

```

```

end SCS_ID_S;

```

```

end SCS_ID;

```

```

constant SIZE equals .;

```

```

end CLMACK_MESSAGE;

```



```

/**
/* Connection manager messages. These messages are sent from cluster
/* connection management to the OPCOM process on the local node.
/*-

```

```

/*
/* Define header for all CNXMAN messages.
/*

```

```

aggregate CNXMAN_MESSAGE structure prefix CNM_ fill;

```

```

RQSTCODE    byte unsigned;      /* OPCSB RQSTCODE (value OPC$ X_CNXMAN)
CNM_CODE     byte unsigned;      /* CNXMAN-specific request code
DS_VERSION   byte unsigned;      /* Version of data structure
SW_VERSION   byte unsigned;      /* Version of CNXMAN software
LENGTH       word unsigned;      /* Total length (including extensions)
fill_1       word unsigned;      /* spare word */
CSID         longword unsigned;   /* CSID associated with message
SCS_ID union fill;
  SYSTEMID    character length 6; /* 48 bit SCS System ID
  SCS_ID_S structure fill;
    SYSTEMIDL  longword unsigned; /* Low order longword
    SYSTEMIDH  word unsigned;     /* High order word
  end SCS_ID_S;
end SCS_ID;
SCSNODE structure quadword unsigned; /* Quadword buffer for node name
SCSNODEL     longword unsigned;      /* Low order name
SCSNODEH     longword unsigned;      /* High order name
end SCSNODE;

```

```

constant SIZE equals .;

```

```

end CNXMAN_MESSAGE;

```

```
/*
/* Define message fields for a particular connection manager message. The
/* CNM_B_CNM_CODE field in the header implies the appropriate message
/* extension.
/*
aggregate xxx_MESSAGE structure prefix xxx_ fill;
    CNM_HEADER character length CNM_K_SIZE fill;
    constant DS_VERSION equals 1;          /* Gives us xxx_K_DS_VERSION
    /*
    constant MIN_SIZE equals .;            /* Min message size
    constant SIZE equals .;               /* Total message size
end xxx_MESSAGE;
```



OPCOMDEF.SDL;1

16-SEP-1984 16:43:05.73 Page 23

end\_module OPCOMDEF;

OP

EX

EX

EX

EX



0288 AH-BT13A-SE  
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION  
CONFIDENTIAL AND PROPRIETARY

